



US008576976B2

(12) **United States Patent**
Singh et al.

(10) **Patent No.:** **US 8,576,976 B2**
(45) **Date of Patent:** **Nov. 5, 2013**

(54) **APPARATUS FOR SUPPORTING
RADIOACTIVE FUEL ASSEMBLIES AND
METHODS OF MANUFACTURING THE
SAME**

(75) Inventors: **Krishna P. Singh**, Jupiter, FL (US);
Stephen J. Agace, Marlton, NJ (US)

(73) Assignee: **Holtec International, Inc.**

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 613 days.

3,844,886 A *	10/1974	Crowther	376/267
4,039,842 A	8/1977	Mollon	
4,084,363 A *	4/1978	Moore	52/309.4
4,096,392 A	6/1978	Rubinstein et al.	
4,124,445 A	11/1978	Mollon	
4,218,622 A	8/1980	McMurtry et al.	
4,225,467 A	9/1980	McMurtry et al.	
4,287,145 A	9/1981	McMurtry et al.	
4,382,060 A	5/1983	Holtz et al.	
4,581,201 A	4/1986	Haggstrom et al.	
4,610,893 A	9/1986	Eriksson et al.	
4,626,402 A	12/1986	Baatz et al.	
4,634,875 A *	1/1987	Kugeler et al.	250/506.1

(Continued)

(21) Appl. No.: **12/260,914**

(22) Filed: **Oct. 29, 2008**

(65) **Prior Publication Data**

US 2009/0175404 A1 Jul. 9, 2009

Related U.S. Application Data

(60) Provisional application No. 60/983,566, filed on Oct.
29, 2007, provisional application No. 61/038,525,
filed on Mar. 21, 2008.

(51) **Int. Cl.**
G21C 19/40 (2006.01)

(52) **U.S. Cl.**
USPC **376/272; 250/506.1**

(58) **Field of Classification Search**
USPC **376/272; 250/506.1**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,415,274 A *	5/1922	Stowell	52/569
2,426,943 A *	9/1947	Morden	52/474
2,968,734 A *	1/1961	Yeomans	378/67

FOREIGN PATENT DOCUMENTS

DE	3216855 A1	11/1983
EP	0626699 A1	11/1994

(Continued)

OTHER PUBLICATIONS

<http://www.easyrenovate.com/why-stagger-end-joints-on-subflooring/>, accessed Jul. 4, 2011.*

(Continued)


Primary Examiner — Timothy A Brainard

(74) *Attorney, Agent, or Firm* — The Belles Group, P.C.

(57) **ABSTRACT**

Apparatus for supporting radioactive fuel assemblies, such as spent nuclear fuel. In one aspect, the invention is an apparatus, which can be in the form of a fuel basket, fuel rack, or the like, in which hexagonal storage tubes are used not only for their internal cells but are also strategically patterned to create resultant cells with their outside surfaces. In another aspect, the invention is an apparatus having flux traps surrounding each cell wherein the size of the flux traps decrease with distance from the center of the storage grid.

19 Claims, 24 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,666,659 A 5/1987 Lusk et al.
 4,788,029 A 11/1988 Kerjean
 4,988,473 A 1/1991 Mueller et al.
 4,997,618 A 3/1991 Efferding
 5,009,837 A * 4/1991 Nguyen et al. 376/261
 5,019,327 A 5/1991 Fanning et al.
 5,032,348 A 7/1991 Blum et al.
 5,063,299 A 11/1991 Efferding
 5,198,183 A 3/1993 Newman
 5,232,657 A 8/1993 Kovacik et al.
 5,245,641 A 9/1993 Machado et al.
 5,291,532 A 3/1994 Townsend et al.
 5,361,281 A 11/1994 Porowski
 5,365,556 A 11/1994 Mallie
 5,431,295 A * 7/1995 Meess 220/62.15
 5,438,597 A 8/1995 Lehnert et al.
 5,479,463 A 12/1995 Roberts
 5,629,964 A 5/1997 Roberts
 5,651,038 A 7/1997 Chechelnitsky et al.
 5,715,289 A * 2/1998 Kirchner et al. 376/272
 5,841,825 A 11/1998 Roberts
 5,887,042 A 3/1999 Akamatsu et al.
 5,898,747 A 4/1999 Singh
 5,914,994 A 6/1999 Wasinger et al.
 5,965,829 A 10/1999 Haynes et al.
 6,042,779 A 3/2000 Oschmann et al.
 6,064,710 A 5/2000 Singh
 6,283,028 B1 9/2001 Walczak
 6,327,321 B1 12/2001 Holman
 6,442,227 B1 8/2002 Iacovino, Jr. et al.
 6,665,365 B2 * 12/2003 Dallongeville et al. 376/272
 6,741,669 B2 5/2004 Lindquist
 6,839,395 B2 1/2005 Ohsono et al.
 6,878,952 B1 4/2005 Ohsono et al.
 6,989,543 B2 * 1/2006 Drobnik et al. 250/455.11
 7,194,060 B2 3/2007 Ohsono et al.
 2002/0118786 A1 8/2002 Ohsono et al.
 2002/0163989 A1 * 11/2002 Dallongeville et al. 376/272

2003/0140471 A1 7/2003 Busnardo et al.
 2003/0179846 A1 9/2003 Murakami et al.
 2004/0062338 A1 4/2004 Ohsono et al.
 2004/0140307 A1 7/2004 Canzler et al.
 2005/0117688 A1 * 6/2005 Ohsono et al. 376/272
 2005/0135541 A1 6/2005 Ohsono et al.
 2005/0157833 A1 7/2005 Ishihara et al.
 2005/0188523 A1 9/2005 Busnardo et al.
 2005/0224729 A1 10/2005 Tamaki
 2005/0286674 A1 12/2005 Fischer et al.
 2006/0109945 A1 5/2006 Ohsono et al.
 2007/0034541 A1 2/2007 Danko et al.
 2007/0133734 A1 * 6/2007 Fawcett et al. 376/438
 2007/0153965 A1 7/2007 Choi et al.
 2008/0031396 A1 * 2/2008 Singh et al. 376/272
 2008/0031397 A1 2/2008 Singh et al.
 2008/0049886 A1 2/2008 Lahille et al.
 2008/0069291 A1 3/2008 Singh et al.
 2009/0172961 A1 7/2009 Lahille
 2009/0175404 A1 7/2009 Singh et al.
 2009/0185652 A1 7/2009 Tamaki et al.
 2011/0033019 A1 2/2011 Rosenbaum et al.
 2011/0038449 A1 2/2011 Shin et al.
 2011/0122985 A1 5/2011 Tamaki

FOREIGN PATENT DOCUMENTS

JP 01237499 9/1989
 JP 0712985 A 1/1995
 WO WO2008063708 5/2008

OTHER PUBLICATIONS

A. Machiels, Qualification of Metamic for Spent-Fuel Storage Application, EPRI Final Report Oct. 2001.
 What is Metamic web article, <http://www.metamic.com/whatismetamic.htm>, copyright 2004, Metamic, LLC.
 S.M. Barinov et al., Crack Resistance of Cermets Aluminum Oxide—Chromium, Institute of Metallurgy, Academy of Sciences of the USSR, No. 5(341), pp. 98-101, May 1991.

* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6A




FIGURE 6B




FIGURE 7




FIGURE 8




FIGURE 9







FIGURE 10






FIGURE 12




FIGURE 13




FIGURE 14




FIGURE 15




FIGURE 16




FIGURE 17




FIGURE 18




FIGURE 19




FIGURE 20




FIGURE 21




FIGURE 22




FIGURE 23




FIGURE 24

**APPARATUS FOR SUPPORTING
RADIOACTIVE FUEL ASSEMBLIES AND
METHODS OF MANUFACTURING THE
SAME**

CROSS-REFERENCE TO RELATED PATENT
APPLICATIONS

The present application claims the benefit of U.S. Provisional Patent Application Ser. No. 60/983,566, filed Oct. 29, 2007 and U.S. Provisional Patent Application Ser. No. 61/038,525, filed Mar. 21, 2008, the entireties of which are hereby incorporated by reference.

FIELD OF THE INVENTION

The present invention relates generally to apparatus and methods for supporting high level radioactive waste and specifically to apparatus and methods for supporting radioactive fuel assemblies. The subject inventions can be implemented into a wide variety of structures for transferring, supporting and/or storing spent nuclear fuel assemblies, including without limitation underwater fuel racks and fuel baskets incorporated into either canisters or casks.

BACKGROUND OF THE INVENTION

In the nuclear power industry, the nuclear energy source is in the form of hollow zircaloy tubes filled with enriched uranium, known as fuel assemblies. Upon being deleted to a certain level spent fuel assemblies are removed from a reactor. At this time, the fuel assemblies not only emit extremely dangerous levels of neutrons and gamma photons (i.e., neutron and gamma radiation) but also produce considerable amounts of heat that must be dissipated.

It is necessary that the neutron and gamma radiation emitted from the spent fuel assemblies be adequately contained at all times upon being removed from the reactor. It is also necessary that the spent fuel assemblies be cooled. Because water is an excellent radiation absorber, spent fuel assemblies are typically submerged under water in a pool promptly after being removed from the reactor. The pool water also serves to cool the spent fuel assemblies by drawing the heat load away from the fuel assemblies. The water may also contain a dissolved neutron shielding substance.

The submerged fuel assemblies are typically, supported in the fuel pools in a generally upright orientation in rack structures, commonly referred to as fuel racks. It is well known that neutronic interaction between fuel assemblies increases when the distance between the fuel assemblies is reduced. Thus, in order to avoid criticality (or the danger thereof) that can result from the mutual inter-reaction of adjacent fuel assemblies in the racks, it is necessary that the fuel racks support the fuel assemblies in a spaced manner that allows sufficient neutron absorbing material to exist between adjacent fuel assemblies. The neutron absorbing material can be the pool water, a structure containing a neutron absorbing material, or combinations thereof.

Fuel racks for high density storage of fuel assemblies are commonly of cellular construction with neutron absorbing plate structures (i.e., shields) placed between the cells in the form of solid sheets. The cells are usually long vertical square tubes which are open at the top through which the fuel elements are inserted. The cells are sometimes with double walls that encapsulate the neutron shield sheets to protect the neutron shield from corrosion or other deterioration resulting from contact with water.

Each fuel assembly is placed in a separate cell so that the fuel assemblies are shielded from one another. An example of a typical existing fuel rack, is described in U.S. Pat. No. 4,382,060, to Maurice Holtz et al., issued May 3, 1983, the entirety of which is hereby incorporated by, reference. The Holtz rack is comprised of structural elements including elements which are hollow and cruciform in section. Each leg of the cruciform structural element includes a neutron shield therein. The free end of the legs or the cruciform structural element converge so as to have an included angle of approximately 90 degrees. The rack is comprised of such cruciform elements as well as cooperating elements which are generally T and L shaped in section.

In certain regions of the world, the fuel assemblies used in the nuclear reactors do not have a rectangular horizontal cross-section. Instead, the fuel assemblies have a horizontal cross-section that is generally hexagonal. In such instances, existing racks having cells with rectangular horizontal cross-sections are less than optimal.

Even after removal from the pool, the fuel assemblies still emit extremely dangerous neutrons (i.e., neutron radiation) and gamma photons (i.e., gamma radiation) and it is thus still imperative that these neutrons and gamma photons be contained at all times during transfer and storage. It also imperative that the residual heat emanating from the fuel assemblies be lead away and escape from the fuel assemblies. Thus, containers used to transfer and/or store fuel assemblies must not only safely enclose and absorb the radioactivity of the fuel assemblies, they must also allow for adequate cooling. In the art, there are two type of container systems used to transport and/or store fuel assemblies, canister-based systems and cask-based systems.

Generally speaking, there are two types of casks used for the transportation and/or storage of SNF, ventilated vertical overpacks ("VVOs") and thermally conductive casks. VVOs typically utilized in conjunction with a sealable canister that is loaded with the fuel assemblies and positioned within a cavity of the VVO. Such canisters, which are often multi-purpose canisters, often contain a fuel basket for receiving the fuel assemblies. An example of a canister and basket assembly designed for use with a VVO is disclosed in U.S. Pat. No. 5,898,747 (Singh), issued Apr. 27, 1999, the entirety of which is hereby incorporated by reference. The second type of casks are thermally conductive casks. In a typical thermally; conductive cask, the fuel assemblies are loaded directly into a cavity formed by the cask body. A basket assembly is typically provided within the cavity itself to provide support for the fuel assemblies.

The fuel basket generally acts in conjunction with the cask to support the fuel in a particular pattern, minimize load transfer to the fuel, transfer heat to the cask and control criticality.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a fuel rack that can safely accommodate fuel assemblies.

Yet another object of the present invention is to provide a fuel rack having a horizontal cross-section that is non-rectangular in shape, such as hexagonal.

Still another object of the present invention is to provide a fuel rack that is cost effective to manufacture.

A further object of the present invention is to provide a fuel rack that can withstand high inertia loads acting in concert with hydraulic loads from moving water.

A yet further object of the present invention is to provide a fuel rack that allows natural thermosiphon flow of the pool water through the cells.

A still further object of the present invention is to provide a fuel rack that eliminates the need for neutron absorber plates.

It is a further object of the present invention to provide a fuel rack constructed of slotted plates.

Another object of the present invention is to provide a fuel rack that is compact and maximizes the storage space of a fuel pool.

A yet further object of the present invention is to provide a fuel rack that resists water corrosion.

Still another object of the present invention is to provide a fuel rack that maintains structural stability under radiation exposure.

Another object of the present invention is to provide a fuel rack that provides flux traps.

It is an object of the present invention to provide a fuel basket that provides higher structural integrity.

It is a further object of the present invention to provide a fuel basket that has fuel cells which correspond to the shape of the fuel assembly to be stored therein.

A yet further object of the present invention is to provide a fuel basket that maximizes the packing density of the spent nuclear fuel while maintaining a reactivity of 0.95 or less.

A yet further object of the present invention is to provide a fuel basket that is easy to manufacture and lightweight.

These and other objects are met by the present invention which, in one aspect can be a fuel rack having an array of cells for holding fuel assemblies comprising: a base plate having a top surface; a plurality of tubes, each tube having an inner surface that forms one of the cells; and the tubes connected to the top surface of the base plate in a substantially vertical orientation and in a pattern so that one or more of the cells are formed by outside surfaces of the adjacent tubes.

In another aspect, the invention can be a fuel rack for supporting fuel assemblies comprising: a plurality of hexagonal tubes having an internal cavity; a base plate having a top surface; the hexagonal tubes connected to the top surface of the base plate in a substantially vertical orientation and spaced from one another so that a flux trap space exists between all adjacent hexagonal tubes; and a plurality of spacers positioned in the flux trap spaces for maintaining the existence of, the flux trap spaces, the spacers connected to the hexagonal tubes.

In yet another aspect, the invention can be a fuel rack having an array of cells for holding fuel assemblies comprising a plurality of slotted plates that are slidably interlocked with one another to form the array of cells.

In another aspect, the invention can be a fuel basket having a honeycomb-like grid that forms a plurality of substantially vertically oriented elongated cells. Most preferably, the basket assembly comprises one or more flux traps and is positioned within the cavity. The basket assembly can be constructed of a metal matrix composite material. In one embodiment, the basket assembly may utilize variable flux traps to maximize packing density. In such an embodiment, as the periphery of the basket assembly is approached, the width of the flux traps may decrease. In another embodiment, the basket assembly may utilize tubular elements of varying heights in a vertically staggered formation so that no two adjacent cells have interfaces which are vertically aligned.

In a further aspect, the invention can be an apparatus for supporting radioactive fuel assemblies comprising a grid of cells for housing radioactive fuel assemblies, the grid formed by a plurality of hexagonal tubes having an outer surface and

an inner surface that forms one of the cells, the plurality of hexagonal tubes arranged in an adjacent manner and in a pattern so that one or more of the cells is a resultant cell formed by the outside surfaces of surrounding hexagonal tubes.

In a yet further aspect, the invention can be an apparatus for supporting radioactive fuel assemblies comprising: a grid of cells for housing radioactive fuel assemblies, the grid formed by a plurality of tubes having inner surfaces that form the cells, the tubes arranged in an axially aligned and adjacent manner; each of the tubes formed by a plurality of tubular segments stacked in axial alignment, an interface formed between the adjacent tubular segments of each tube; and wherein the lengths of the tubular segments and the pattern in which the tubes are arranged to form the grid is such that none of the interfaces of adjacent tubes are aligned with one another.

In a still further aspect, the invention can be an apparatus for supporting radioactive fuel assemblies comprising: a bottom section comprising a plurality of bottom tubular segments of varying length, the bottom tubular segments arranged in an axially adjacent manner and in a pattern so that no two adjacent bottom tubular segments are the same length, the bottom edges of the bottom tubular segments being aligned; at least one middle section comprising a plurality of middle tubular segments of equal length, the middle section stacked atop the bottom section so that the middle tubular segments are axially aligned with the bottom tubular segments and the bottom edges of the middle tubular segments about the top edges of the bottom tubular segments; and a top section comprising a plurality of top tubular segments of varying length, the top section stacked atop the middle section so that the top tubular segments are axially aligned with the middle tubular segments, the bottom edges of the top tubular segments about the top edges of the bottom tubular segments, and the top edges of the top tubular segments are aligned.

In even another aspect, the invention can be a fuel rack having a grid of cells for holding fuel assemblies comprising: a base plate having a top surface; a plurality of hexagonal tubes, each hexagonal tube having inner surfaces that forms one of the cells; and the hexagonal tubes connected to the top surface of the base plate in a substantially vertical orientation and in a pattern so that one or more of the cells are formed by outside surfaces or the adjacent hexagonal tubes.

In yet another aspect, the invention can be a fuel rack having a grid of cells for holding fuel assemblies comprising: a base plate having a top surface; a plurality of tubes, each tube having an inner surface that forms one of the cells; and the tubes connected to the top surface of the base plate in a substantially vertical orientation and in a pattern so that one or more of the cells are formed by outside surfaces of the adjacent tubes.

In still another aspect, the invention can be a fuel rack for supporting fuel assemblies comprising: a plurality of hexagonal tubes having an internal cavity; a base plate having a top surface; the hexagonal tubes connected to the top surface of the base plate in a substantially vertical orientation and spaced from one another so that a flux trap space exists between all adjacent hexagonal tubes; and a plurality of spacers positioned in the flux trap spaces for maintaining the existence of the flux trap spaces, the spacers connected to the hexagonal tubes.

In another aspect, the invention can be a fuel rack for supporting fuel assemblies comprising: a plurality of tubes having an internal cavity; a base plate having a top surface; the tubes connected to the top surface of the base plate in a

substantially vertical orientation and spaced from one another so that a flux trap space exists between all adjacent tubes; and a plurality of spacers positioned in the flux trap spaces for maintaining the existence of the flux trap spaces, the spacers connected to the tubes.

In a still further aspect, the invention can be a fuel rack having perimeter cells and non-perimeter cells for supporting fuel assemblies comprising: a base plate having a top surface; a plurality of hexagonal tubes, each hexagonal tube having inner surfaces that form one of the perimeter cells or the non-perimeter cells; and the hexagonal tubes connected to the top surface of the base plate in a substantially vertical orientation and in a pattern so that even third non-perimeter cell is formed by outside surfaces of six surrounding hexagonal tubes.

In yet another aspect, the invention can be a fuel basket for supporting radioactive fuel assemblies comprising: a plurality of tubes having an internal cavity for receiving a radioactive fuel assembly; the tubes arranged in a substantially vertical orientation and spaced from one another so that a flux trap space exists between all adjacent tubes, the tubes forming a storage grid having a central axis and a perimeter; a plurality of spacers positioned in the flux trap spaces for maintaining the existence of the flux trap spaces; and wherein the width of the flux trap space between adjacent tubes decreases with distance from the central axis of the storage grid.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top perspective view of a fuel rack according to one embodiment of the invention.

FIG. 2 is a close up view of a top portion of the fuel rack of FIG. 1.

FIG. 3 is a top view of the fuel rack of FIG. 1.

FIG. 4 is a bottom perspective view of the fuel rack of FIG. 1.

FIG. 5 is a close-up view of a bottom corner of the fuel rack of FIG. 1.

FIG. 6A is a top perspective view of an adjustable height pedestal removed from the fuel rack of FIG. 1.

FIG. 6B is a bottom perspective view of the adjustable height pedestal of FIG. 6A.

FIG. 7 is a top perspective view of a fuel rack according to a second embodiment of the invention that includes flux traps.

FIG. 8 is a close up view of a top portion of the fuel rack of FIG. 7.

FIG. 9 is a top view of the fuel rack of FIG. 7.

FIG. 10 is a top perspective view of a fuel rack according to one embodiment of the invention that is constructed of a slotted plates.

FIG. 11A is a perspective view of first slotted plate used in the construction of the fuel rack of FIG. 10.

FIG. 11B is a perspective view of a second slotted plate used in the construction of the fuel rack of FIG. 10.

FIG. 11C is a perspective view of a third slotted plate used in the construction of the fuel rack of FIG. 10.

FIG. 12 is a perspective view of a vertical section of slotted plates of the fuel rack of FIG. 10.

FIG. 13 is a top perspective view of a storage grid portion of a fuel basket according to an embodiment of the present invention.

FIG. 14 is a top view of the area II-II of FIG. 13 illustrating a resultant cell according to one embodiment of the present invention.

FIG. 15 is a perspective view of the bottom vertical segments of the storage tubes of the fuel basket of FIG. 13

arranged in the desired pattern so that interfaces between segments of adjacent storage tubes are not vertically aligned.

FIG. 16 is a top view of a fuel basket according to one embodiment of the present invention, comprising the storage grid portion of FIG. 13 and perimeter support tubes.

FIG. 17 is a perspective view of the supports tubes according to one embodiment of the present invention.

FIG. 18 is a perspective view of the fuel basket of FIG. 16.

FIG. 19 is a perspective view of a fuel basket assembly according to a second embodiment of the present invention.

FIG. 20 is a perspective view of a storage tube of the fuel basket of FIG. 19.

FIG. 21 is a perspective view of the bottom vertical segment of the storage grid portion of the fuel basket of FIG. 19.

FIG. 22 is a bottom perspective view of the storage grid portion of the fuel basket of FIG. 19.

FIG. 23 is a top perspective view of the storage grid portion of the fuel basket of FIG. 19.

FIG. 24 is a top view of the fuel basket of FIG. 19.

DETAILED DESCRIPTION OF THE DRAWINGS

The present invention will now be described in relation to exemplary embodiments. It is to be understood that while certain details and structural arrangements are explained in detail with respect to a certain embodiment, the details and structural arrangements can be implemented into any of the embodiments.

I. Flux Trap Fuel Rack Embodiment

Referring to FIG. 1, a perspective view of a fuel rack 100 according to one embodiment of the present invention is disclosed. The fuel rack 100 is a cellular, upright prismatic module. The illustrated embodiment of the fuel rack 100 is specifically designed to accommodate hexagonal fuel assemblies, such as VVER 1000 fuel assemblies. To this extent, each cell 101 of the fuel rack 100 is also generally hexagonal in shape (i.e., have a hexagonal horizontal cross-section) so as to geometrically, accommodate a single hexagonal fuel assembly. However, it is to be understood that the concepts of the present invention can be modified to accommodate any shaped fuel assembly, including rectangular, octagonal, round, etc.

In describing the fuel rack 100 and its component parts below, relative terms such as top, bottom, above, below, horizontal, vertical upper and lower will be used in relation to the fuel rack 100 being in the illustrated substantially vertical orientation of FIG. 1. Additionally, in order to avoid clutter in the drawings, only a few of each component are numbered with the understanding that the reader will be able to identify duplicate elements.

The fuel rack 100 generally comprises a base plate 110, a plurality of hexagonal tubes 120, and a plurality of spacing rods 130 (best visible in FIG. 2). The hexagonal tubes 120 are connected to the top surface 111 of the base plate 110 in a substantially vertical orientation. In this embodiment, the axis of each hexagonal tube 120 is not only substantially vertical but also substantially perpendicular to the top surface 111 of the base plate 110. The connection between the hexagonal tubes 120 and the base plate 110 is achieved by welding the bottom edge of the hexagonal tubes 120 to the top surface of the base plate 110. Of course, other connection techniques can be utilized with minor modification, including mechanical connections such as bolting, clamping, threading, etc.

The top ends of the hexagonal tubes 120 remain open so that a fuel assembly can be slid into the internal cavity 101 (also referred to as a cell) formed by the inner surfaces of the

hexagonal tubes **120**. Each hexagonal tube **120** can be a single-part tube that extends the entire desired height H_1 or can be constructed of multiple partial height tubes that together add up to the desired height H_1 . It is preferred that the height H_1 be sufficient so that the entire height of the fuel assembly is within the hexagonal tube **120**.

The hexagonal tubes **120** are connected to the rectangular base plate **110** in an adjacent and spaced pattern to form a honeycomb-like grid of the cells **101**. The cells **101** are substantially vertical elongated cavities for receiving the radioactive fuel assemblies via their open top ends. While a generally rectangular gridwork of cells **101** is illustrated, the fuel rack **100** can be designed to take on any desired shape. The geometric arrangement of the hexagonal tubes **120** will be discussed in greater detail below with respect to FIGS. 2-3.

The hexagonal tubes **120** preferably constructed of a metal-matrix composite material, and more preferably a discontinuously reinforced aluminum/boron carbide metal matrix composite material, and most preferably a boron impregnated aluminum. One such suitable material is sold under the tradename Metamic™. The hexagonal tubes **120** perform the dual function of reactivity control as well as structural support. The base plate **110** is preferably, constructed of a metal that is metallurgically compatible with the material of which the hexagonal tubes **120** are constructed for welding.

Referring now to FIGS. 2-3 concurrently, each hexagonal tube **120** is arranged so as to be spaced from all adjacent hexagonal tubes **120** so that a gap **140** exists between each hexagonal tube **120** and its immediately adjacent hexagonal tubes **120**. The gap **140** acts a neutron flux trap that decreases and/or eliminates the danger of criticality. The flux trap space **140** can be designed to be any desired width and the exact width will depend on the radiation levels of the fuel assemblies to be stored, the material of construction of the tubes **120**, and properties of the pool water in which the fuel rack **100** will be submerged. In one embodiment, the flux trap spaces **140** will have a width between 30 and 50 millimeters and more preferably between 25 to 35 millimeters and most preferably about 38 millimeters.

Spacers, which are in the form of spacing rods **130** in the illustrated embodiment, are inserted into the flux trap spaces **140** so as to maintain the existence of the flux trap spaces **140** at the desired width and to provide added structural stability. While the spacers are illustrated as elongated rods **130** that extend the entire height H_1 of the hexagonal tubes **120**, the spacers are not so limited and can take on a wide variety of shapes and sizes. For example, the spacers could be merely blocks or pins if desired in some embodiments.

A spacing rod **130** is positioned at the juncture between the edges of three adjacent hexagonal tubes **120**. Thus, each spacing rod **130** (with the exception of those spacing rods **130** along the perimeter) contacts three hexagonal tubes **120**. For added integrity and ease of construction, the spacing rods **130** have three axial grooves along their length that act as nesting volumes for receiving the edge of the hexagonal tubes **120**. In the illustrated embodiment, the spacing rods **130** have a horizontal cross-section that is generally in the shape of a truncated triangle, wherein a nesting groove is formed into each truncated apex. Of course, the spacing rods **130** can take on other shapes with or without the grooves.

The spacing rods **130** are preferably made of aluminum or a metal matrix material, such as boron impregnated aluminum. The spacing rods **130** are plug welded to the hexagonal tubes **120** in which the %, are in contact with via elongated holes **121** located at the edges/corners of the hexagonal tubes **120**. The shape, location and number of plug weld holes **120**

will vary depending on design considerations and is in no way limiting of the present invention. The plug holes **121** are uniformly on each corner of the hexagonal tubes **120** to facilitate uniform manufacture but this is not necessary. The plug holes **121** can be formed by punching, cutting, or during a molding process.

Referring now to FIGS. 3-4 concurrently, the base plate **110** also comprises a plurality of flow holes **115** extending through the base plate **110** from its bottom surface **112** to its top surface **111**. Similarly, the base plate **110** also comprises four oblong holes **116** (second row in from the corners) for lifting and installing the fuel rack **100** within the fuel pool. A special lifting beam with four long reach rods is used to interact with the oblong holes **116** to grapple the fuel rack **100** and place it in the pool.

The flow holes **115** (and oblong holes **116**) create passageways from below the base plate **100** into the cells **101** formed by the hexagonal tubes **120**. Preferably, a single flow hole **115** is provided for each cell **101**. The flow holes **115** are provided as inlets to facilitate natural thermosiphon flow of pool water through the cells **101** when fuel assemblies having a heat load are positioned therein. More specifically, when heated fuel assemblies are positioned in the cells **101** in a submerged environment, the water within the cells **101** surrounding the fuel assemblies becomes heated, thereby rising due to increased buoyancy. As this heated water rises and exits the cells **101** via their open top ends, cool water is drawn into the bottom of the cells **101** via the flow holes **115**. This heat induced water flow along the fuel assemblies then continues naturally.

As can best be seen in FIG. 5, a plurality of auxiliary cutouts/holes **121** are provided in the hexagonal tubes **120** at or near their bottom edge. The auxiliary holes **121** act as additional inlet openings for incoming pool water to facilitate the thermosiphon flow during the cooling process. Moreover, as will be described below, the flow holes **115** of certain cells **101** are blocked by the attachment of adjustable height pedestals **150**. The auxiliary holes **121** of the hexagonal tubes **120** that form these cells **101** are thus the sole source of incoming cool water for fuel assemblies stored therein. While an auxiliary hole **121** is provided in each face of each and every hexagonal tube **120** in the fuel rack **100**, it is to be understood that this may not be necessary in all instances.

As a side note, the flow holes **115** (and holes **116**) perform an additional function of providing an access-way into to the cells **101** for a "goose-neck welder" for welding the hexagonal tubes **120** to the top surface of the base plate **110**.

Referring back to FIGS. 3-4, the base plate **110** also comprises a plurality, of adjustable height pedestals **150** connected to the bottom surface **112** of the base plate **110**. The adjustable height pedestals **150** ensure that a space exists between the floor of the fuel pool and the bottom surface **112** of the base plate **110**, thereby creating an inlet plenum for water to flow through the flow holes **115**.

The adjustable height pedestals **150** are spaced to provide uniform support of the base plate **110** and thus the fuel rack **100**. Each pedestal **150** is individually adjustable to level and support the rack on a non-uniform spent fuel pool floor. The pedestals **150** are bolted to the base plate **110**. Of course, if desired, the pedestals **150** can be attached to the base plate **110** by other means, including welding or threading. In the event of welded pedestal **150**, an explosion-bonded stainless-Aluminum plate may be used to make the transition. For a welded pedestal, the bolts and bolt holes are eliminated.

Referring now to FIGS. 6A-6B, the construction details of the adjustable height pedestals **150** will be described. Each of the adjustable height pedestals **150** comprises a block **151** and

a cylindrical peg **152** that acts as the foot. The block **152** is connected to the base plate **110** via bolts **155**.

The block **151** comprises a central hole **153** which has a threaded inner surface (not visible). Similarly, the outer surface of a portion of the peg **151** is also threaded with corresponding threads. The peg **152** is inserted into the hole **153** and threadably engaged therein to the block **151**.

The peg **152** also comprises a rectangular depression **154** in its top surface for receiving a tool for turning the peg **152**. Of course, the depression can be any shape that will facilitate rotational engagement with a tool. Moreover, other means for engaging and turning the peg **152** can be used including a tab, a screw head, a bolt head, etc.

Because of the threaded connection between the peg **152** and the block **151**, turning the peg **152** via the depression **154** results in increasing or decreasing the height the peg **152** protrudes from the bottom surface of the block **151**. Adjustment of the peg **152** is facilitated by a long-handled tool that is inserted into the cell **101**. The depression **154** of the peg **152** is accessible through the flow hole **115** in that cell **101** (see FIG. 3).

The bottom portion of the peg **152** has a rounded edge to prevent catching and tearing of the liner in a seismic-induced slide of the fuel rack **100**. A break in the liner means problems for the site because of leakage. If desired, the bottom surface of the peg **152** can be formed or covered with a low friction sliding material.

II. Non-Flux Trap Fuel Rack Embodiment Incorporating Resultant Cells

Referring now to FIGS. 7-10 concurrently, a second embodiment of a fuel rack **200** is illustrated. Similar to the rack above, the fuel rack **200** is a cellular, upright, prismatic module. The illustrated embodiment of the fuel rack **200** is specifically designed to accommodate hexagonal fuel assemblies, such as VVER **1000** fuel assemblies. Each cell **201** of the fuel rack **200** is also generally hexagonal in shape (i.e., have a hexagonal horizontal cross-section) so as to geometrically accommodate a single hexagonal fuel assembly. However, it is to be understood that the concepts of the present invention can be modified to accommodate any shaped fuel assembly, including rectangular, octagonal, round, etc.

In describing the fuel rack **200** and its component parts below, relative terms such as top, bottom, above, below, horizontal, vertical upper and lower will be used in relation to the fuel rack **200** being in the illustrated substantially vertical orientation of FIG. 7. Additionally, in order to avoid clutter in the drawings, only a few of each component are numbered with the understanding that the reader will be able to identify duplicate elements.

The driving factor that leads to the structural differences between fuel rack **100** (discussed above) and the fuel rack **200** is that the fuel rack **200** is designed to be used with fuel assemblies that do not require the presence of a neutron flux trap between adjacent cells **201**. Thus, the inclusion of neutron flux traps in fuel racks when not needed is undesirable because valuable pool floor area is unnecessarily wasted. Of course, both fuel rack types **100**, **200** may be stored side by side in the same pool.

Because many of the structural and functional features of the fuel rack **200** are identical to the fuel rack **100**, only those aspect of the fuel rack **200** that are different will be discussed below with the understanding that the other concepts discussed above with respect to fuel rack **100** are applicable.

The fuel rack **200** comprises a plurality of hexagonal tubes **220**. The hexagonal tubes **220** are connected to the top surface **211** of the base plate **210** in a substantially vertical orientation. In this embodiment, the axis of each hexagonal tube **220**

is not only substantially vertical but also substantially perpendicular to the top surface **211** of the base plate **210**. The connection between the hexagonal tubes **220** and the base plate **210** is achieved by welding the bottom edge of the hexagonal tubes **220** to the top surface of the base plate **110**. Of course, other connection techniques can be utilized with minor modification, including mechanical connections such as bolting, clamping, threading, etc.

The top ends of the hexagonal tubes **220** remain open so that a fuel assembly can be slid into the internal cavity **201A** (also referred to as a cell) formed by the inner surfaces each hexagonal tube **220**. The hexagonal tubes **220** are connected atop the rectangular base plate **110** in a special geometric arrangement so that certain non-perimeter cells **201D** are formed by the outside surfaces of the surrounding hexagonal tubes **220**. Additionally, certain perimeter cells **201B-C** are formed by the outside surfaces of the surrounding hexagonal tubes **220** and an added plate, which depending on the location is either a two-panel plate **225** or a single panel plate **226**.

In other words, the cells **201B-201D** are not the internal cavities of any tubular structures but are resultant cavities formed by either (1) the outer surfaces of the surrounding hexagonal tubes **220**; or (2) the outer surfaces of the surrounding hexagonal tubes **220** and an additional plate structure **225**, **226**. As used herein, all three cell types **201B-201D** will be referred to as "resultant cells" or "developed cells."

Despite their different methods of formation, all of the cells **201A-201D** have a horizontal cross-section that is generally hexagonal. Of course, the result cell concept can be applied to a host of other geometries if desired. The special geometric arrangement of the hexagonal tubes **220** and an additional plate structure **225-226** atop the base plate **210** will now be discussed.

As can best be seen in FIG. 9, the hexagonal tubes **220** are geometrically arranged atop the base plate **210** in rows **1-11** (indicated numerically in a circle). Of course, any number of rows or columns may be created for the fuel rack **200**. The details of the formation of three different kinds of resultant cells will be described in reference to rows **1** through **3** with the understanding that the certain patterns repeat and thus the entire fuel rack **200** can be constructed.

A. Formation of Perimeter Resultant Cells X

The formation of perimeter resultant cells formed by the combination of outside surfaces of the hexagonal tubes and a two-panel plate structure (referred to above as type **201C** cells) will now be described. For ease of reference and to avoid clutter, all perimeter resultant cells formed by the combination of outside surfaces of the hexagonal tubes and a two-panel plate structure are marked with an X.

In row **1**, the hexagonal tubes **220(1)**, **220(2)** are arranged atop the base plate **210** in the top left corner in an adjacent and abutting manner so that the opposing outside surfaces of the hexagonal tubes **220(1)**, **220(2)** are in surface contact. The internal cavities of the hexagonal tubes **220(1)**, **220(2)** act as the first two cells **201A** (not marked). To reduce further clutter, all cells **201A** that are formed by the inner surfaces of a single hexagonal tube **220** are left blank in FIG. 9.

A second pair hexagonal tubes **220(3)**, **220(4)** are arranged atop the base plate **210** within row **1** and spaced from the first pair of hexagonal tubes **220(1)**, **220(2)**. Similar to the first pair of hexagonal tubes **220(1)**, **220(2)**, the second pair of hexagonal tubes **220(3)**, **220(4)** are in arranged in an adjacent and abutting manner so that the opposing outside surfaces of the hexagonal tubes **220(3)**, **220(4)** are in surface contact. While the second pair of hexagonal tubes **220(3)**, **220(4)** are aligned

with the first pair of hexagonal tubes **220(1)**, **220(2)** in row **1**, they are also spaced so as to leave room for a first perimeter resultant cell X.

A two-panel plate structure **225(1)** is connected to the left sides of the hexagonal tubes **220(3)**, **220(4)** to enclose the open lateral side of the perimeter resultant cell X. Specifically, the two panel plate structure **225(1)** is connected to the hexagonal tube **220(2)** and the hexagonal tube **220(3)** by welding or another technique. The perimeter resultant cell X is completed by the outside surfaces of the hexagonal tubes **220(8)**, **220(9)** located in row **2**. Thus a complete hexagonal resulting cell X is formed by the cooperation of the outside surfaces of the hexagonal tubes **220(2)**, **220(3)**, **220(8)**, **220(9)** and the plate structure **225(1)**. The resultant cell X has a horizontal cross-sectional shape that corresponds to the shape of all other cells in the fuel rack **200**.

B. Formation of Resultant Perimeter Cells

The formation of perimeter resultant cells formed by the combination of outside surfaces of the hexagonal tubes and a single-panel plate structure (referred to above as type **201B** cells) will now be described. For ease of reference and to avoid clutter, all perimeter resultant cells formed by, the combination of outside surfaces of the hexagonal tubes and a single-panel plate structure are marked with an #.

Turning now to row **2**, the pair of hexagonal tubes **220(8)**, **220(9)** are arranged atop the base plate **210** in an adjacent and abutting manner with each other and the hexagonal tubes **220(2)**, **220(3)** from row **1**. When so arranged, the opposing outside surfaces of the hexagonal tubes **220(8)**, **220(9)** are in surface contact with one another. The opposing outside surfaces of the hexagonal tubes **220(8)**, **220(2)** are also in surface contact with one another. And, the opposing outside surfaces of the hexagonal tubes **220(9)**, **220(3)** are in surface contact with one another.

The hexagonal tubes **220(14)**, **220(15)** are arranged in row **3** atop the base plate **210** in an adjacent and abutting manner with each other and so that the outside surface of the hexagonal tube **220(15)** is in surface contact with the outside surface of the hexagonal tube **220(8)** from row **2**. A single-panel plate structure **226(1)** is connected to the hexagonal tubes **220(1)**, **220(14)** to enclose the open lateral side of the perimeter resultant cell #. Specifically, the single-panel plate structure **226(1)** is connected to the hexagonal tube **220(1)** and the hexagonal tube **220(14)** by welding or another technique. Thus, a complete hexagonal resulting cell # is formed by the cooperation of the outside surfaces of the hexagonal tubes **220(1)**, **220(2)**, **220(8)**, **220(14)**, **220(15)** and the single-panel plate structure **226(1)**. The resultant cell # has a horizontal cross-sectional shape that corresponds to the shape of all other cells in the fuel rack **200**.

C. Formation of Resultant Perimeter Cells*

The formation of non-perimeter resultant cells formed completely by the cooperation of outside surfaces of the surrounding hexagonal tubes (referred to above as type **201D** cells) will now be described. For ease of reference and to avoid clutter, all non-perimeter resultant cells formed by the cooperation of the outside surfaces of the hexagonal tubes are marked with an*.

In order to avoid redundancy, the arrangement and interaction of the hexagonal tubes atop the base plate will be omitted with the understanding that the discussion above is applicable. In row **2**, a complete hexagonal resulting cell* is formed by the cooperation of the outside surfaces of the hexagonal tubes **220(3)**, **220(4)**, **220(9)**, **220(10)**, **220(16)**, **220(17)**. The resultant cell* has a horizontal cross-sectional shape that corresponds to the shape of all other cells in the fuel rack **200**.

Turning back to the general manufacture and formation of the fuel rack **200**, all connections between the hexagonal tubes **220** and the base plate **210** are accomplished as described above with respect to the fuel rack **100**. Additionally, connections between adjacent hexagonal tubes **220** can be accomplished via the plug holes described above. Furthermore, in order to ensure that the resultant cells **201B-D** are properly sized, the fuel rack may be formed in the following manner.

First, an array of hexagonal tubes **220** are arranged in the desired geometric configuration so that all six outside surfaces of all non-perimeter hexagonal tubes **220** are in contact with the outside surface of the adjacent hexagonal tubes **220**. In other words, at this stage, the fuel rack **200** only comprises cells of the type **201A** that formed by the internal cavities of the hexagonal tubes **220** themselves. However, due to pre-planning, the location of those spots which are to be resultant cells **201B-D** are noted. The array of hexagonal tubes **220** are positioned atop the base plate **210** and the necessary welding is performed. However, any hexagonal tubes **220** that are located in the spots where a resultant cell is desired are not welded to either the base plate **210** or to the adjacent hexagonal tubes **220**. These hexagonal tubes **220** are then slidably removed from the array, thereby leaving the resultant cell **201B-D**. As necessary, the single-panel plates **226** and the two-panel plates **225** are then connected to enclose the perimeter resultant cells **220B-C**.

Furthermore, if desired, neutron absorbing panels can be added to the array as necessary. The fuel rack **200** does not contain an), flux traps.

III. Slotted-Plate Fuel Rack Embodiment

Referring now to FIG. **10**, a fuel rack **300** that is formed from a plurality of slotted-plates arranged in a self-interlocking arrangement is illustrated. The fuel rack **300** is designed so as to have flux traps **340** and rectangular cells **301**. However, it is to be understood that the slotted-plate concept described below can be utilized to form non-flux trap fuel racks and can be utilized to create fuel racks having any shaped cells, including without limitation the fuel racks discussed above.

In describing the fuel rack **300** and its component parts below, relative terms such as top, bottom, above, below, horizontal, vertical upper and lower will be used in relation to the fuel rack **300** being in the illustrated substantially vertical orientation of FIG. **10**. Additionally, in order to avoid clutter in the drawings, only a few of each component are numbered with the understanding that the reader will be able to identify duplicate elements.

Because many of the structural and functional features of the fuel rack **300** are identical to the fuel racks **100**, **200** above, only those aspect of the fuel rack **300** that are different will be discussed below with the understanding that the other concepts and structures discussed above with respect to the fuel racks **100**, **200** are applicable.

The fuel rack **300** generally comprises an array of cells **301** that are formed by a gridwork of slotted plates **370-372** that are slidably assembled in an interlocking rectilinear arrangement. The gridwork of slotted plates **370-372** are positioned atop and connected to a base plate **310**. The entire fuel rack body is formed out of three types of slotted plates, a middle plate **370**, a top plate **371** and a bottom plate **372**. The bottom plate comprises the auxiliary holes **321** as discussed above for facilitating thermosiphon flow into the cells **301**.

Referring now to FIGS. **11A-11C**, one of the middle plates **370**, top plates **371** and bottom plates **372** are illustrated individually. As can be seen, the bottom plate **372** is merely a top half of the middle plate **370** with the auxiliary holes **321**

cutout at its bottom edge. Similarly, the top plate 371 is merely a bottom half of the middle plate 370. The bottom and top plates 372, 371 are only used at the bottom and top of the fuel rack body to cap the middle body segments 380 (FIG. 12) formed from the middle plates 370 so that the fuel rack body has a level top and bottom edge.

Each of the plates 370-372 comprise a plurality of slots 374 and end tabs 375 strategically arranged to facilitate sliding assembly to create the fuel rack body. The slots 374 are provided in both the top and bottom edges of the plates 370-372. The slots 374 on the top edge of each plate 370-372 are aligned with the slots 374 on the bottom edge of that same plate 370-372. The slots 374 extend through the plates 370-372 for one-fourth of the height of the plates 370-372. The end tabs 375 extend from lateral edges of the plates 370-372 and are preferably about one-half of the height of the plates 370-372. The end tabs 375 slidably mate with the indentations 376 in the lateral edges of adjacent plates 370-372 that naturally result from the existence of the tabs 375.

The plates 370-372 are preferably constructed of a metal-matrix composite material, and more preferably a discontinuously reinforced aluminum/boron carbide metal matrix composite material, and most preferably a boron impregnated aluminum. One such suitable material is sold under the trade-name Metamic™.

Referring now to FIG. 12, a single middle segment 380 of the basket is illustrated. Each middle segment 380 of the fuel rack 300 comprises a gridwork of middle plates 370 arranged in a rectilinear configuration so as to form a vertical portion of the cells 301 and the flux traps 340. In creating a middle segment 380, a first middle plates 370 is arranged vertically. A second middle plate 370 is then arranged above and at a generally 90 degree angle to the first middle plate 370 so that its corresponding slots 374 are aligned. The second middle plate 370 is then lowered onto the first middle plate 370, thereby causing the slots 374 to interlock as illustrated. This is repeated with all middle plates 370 until the desired rectilinear configuration is created, thereby creating the segment 380.

In creating the fuel rack body, the slots 374 and end tabs 375 of the segments 380 interlock the adjacent segments 380 together so as to prohibit relative horizontal and rotational movement between the segments 380. The segments 380 intersect and interlock with one another to form a stacked assembly that is the fuel rack body. The fuel rack 300 preferably comprises at least four of the segments 380, and more preferably at least ten segments 380. All of the segments 380 have substantially the same height and configuration.

Therefore, the entire fuel rack 300 is formed of slotted plates 370-372 having what is essentially a single configuration which is the middle plate 370, with the exception that the top and bottom plates 371, 372 have to be formed by cutting the middle plate 370 and adding the cutouts 321.

Furthermore, as a result of the interlocking nature of the slotted plates 370-372, spacers are not needed to maintain the flux traps 340. Thus, in some embodiments, the fuel rack 300 will be free of spacers in the flux traps 340.

IV. Non-Flux Trap Fuel Basket Embodiment

Referring to FIGS. 13-17, a fuel basket 1000 according an embodiment of the present invention is illustrated. The complete and assembled fuel basket 1000 is shown in FIGS. 15 and 17. While the fuel basket 1000 (and its components) are described throughout this specification in conjunction with storing and/or transporting spent nuclear fuel assemblies having a hexagonally shaped horizontal cross-sectional profile, the invention is in no way limited by the type of high level radioactive waste it is use din conjunction with. The fuel

basket assembly 1000 (and its components) can be used to transport and/or store any shape of fuel assemblies.

Referring now to FIG. 13, a perspective view of the storage grid portion 1001 of the fuel basket 1000 is illustrated. The storage grid 1001 is a cellular structure comprising a plurality of tubes 10 forming cells 20 for receiving and holding fuel assemblies. The tubes 10 form a honeycomb-like grid of cells 20 arranged in a polar configuration. For ease of representation (and in order to void clutter), only a few of the tubes 10 and the cells 20 are numerically identified in FIG. 13.

The tubes 10 have a horizontal cross-sectional profile that is hexagonal in shape. The invention is not so limited however, and the tubes 10 will have a horizontal cross-sectional profile that corresponds with the shape of the fuel assembly to be stored within the cavities 20. For example, other polygonal-shaped SNF assemblies may be stored in the fuel basket 1000, in which case the tubes 10 will be of the appropriate horizontal cross-sectional shape. The cells 20 are substantially vertically oriented elongate spaces/cavities having a generally hexagonal horizontal cross-sectional configuration. The horizontal cross-sectional profile of the cells 20 is also not limited to hexagonal, and could be any shape including other polygons. Each cell 20 is designed to accommodate a single fuel assembly. The storage grid 1001 (and thus the cells 20) has a height that is equal to or slightly greater than the height of the fuel assembly for which the basket 1000 is designed to accommodate. The fuel basket 1000 preferably comprises 85 cells 20 and has a weight of approximately 4800 lbs.

Each storage tube 10 comprises five plates 11 having an inner surface 12 and an outer surface 13. The tubes 10 could have less or more plates 11 depending upon the desired horizontal cross-sectional profile. The inner surface 12 of the tubes 10 form the cells 20. Preferably, the tubes 10 are bundled together in an axially adjacent arrangement to form a honeycomb storage grid of cells 20. The tubes 10 are formed by staking tubular segments 10A-10C so as to create cells 20 having a height equal to, or greater than the height of the fuel assembly to be stored therein. An interface/junction 21 is formed between the contacting edges of the tubular segment 10A-10C in each vertical stack that forms the tube 10. For ease of representation (and in order to void clutter), only a few of the contact interfaces are numerically identified in FIG. 13. As will be discussed in further detail below, the tubular segments 10A-10C are of varying height so that the interfaces 21 of adjacent tubes 10/cells 20 are not aligned. By ensuring that the interfaces 21 are not aligned for adjacent tubes 10/cells 207 the structural integrity of the fuel basket 1000 is enhanced.

Preferably, the tubes 10 (and tubular segments 10A-10C) are made by extruding or forming plate stock followed by welding each of the plates 11 at their lateral edges. The tubes 10 are made of a material containing a neutron absorber isotope embedded in the microstructure, such as elemental boron or boron carbide. Metamic, produced by Metamic, LLC, made of an aluminum alloy matrix with embedded boron carbide is an example of an acceptable material. In some embodiments, however, the fuel basket 1000 and its components can be constructed of alternate materials, such as steel or borated stainless steel.

A plurality of cutouts 23 are provided in the plates 11 at the bottom of the tubes 10. For ease of representation (and in order to void clutter), only a few of the cut-outs 23 are numerically identified in FIG. 13. The cutouts 23 form passageways through the plates 11 so that all of the cells 20 are in spatial communication. As a result, the cutouts 23 at or near the bottom of the storage grid 1001 act as a bottom plenum that

helps circulate fluids (air or water) within the fuel basket **1000** (and the cells **20**) to effectuate convective cooling of the stored fuel assemblies during storage and/or transportation. This natural circulation of air or water can be further facilitated by leaving one or more of the cells **20** along the periphery of the basket **100** empty so that they can act as downcomers (the support tubes **30A**, **30B** can also act as downcomers if the cutouts are added). The cutouts **23** are rectangular in shape in the illustrated embodiment but can take on a wide variety of shapes.

Referring to FIGS. **13** and **15** concurrently, the storage grid **1001** is formed by a plurality of sections **150A-D** of the tubular segments **10A-10C** that are arranged in a stacked assembly. The sections **150A-D** and the tubular segments **10A-C** are joined with one another to form the stacked assembly that is the storage grid **1001**. Each section **150A-D** of the storage grid **1001** is a vertical portion of the storage grid **1001** that itself comprises the honeycomb-like grid of tubular segments **10A-C** arranged in the polar configuration. The tubular segments **10A-C** are of three different heights, each different height delineated by the letter A-C. A single bottom section **150A** of the storage grid **1001** is illustrated in FIG. **15**, the bottom section **150A** having tubular segments **10A-C** arranged in a polar configuration. The bottom edges of the tubular segments **10A-C** are aligned at the same elevation. The two middle sections **150B-C** comprise tubular members **10C**, all having the same height. The top section **150D** comprises tubular members **10A-C** arranged so that the top surfaces of the tubular members **10A-C** are aligned at the same elevation.

The tubular segments **10A** have a height that is preferably equal to one foot. The tubular segments **10B** have a height that is preferably equal to two feet. The tubular segments **10C** have a height that is preferably equal to three feet. The invention is not so limited however, and the tubular segments **10A-C** may be of any height so long as the cells formed are at least equal to the height of the fuel assembly. In order to ensure that the interfaces **21** of adjacent tubes **10** are not aligned, it is preferable that no adjacent tubular members **10A-C** of the bottom section **150A** be of the same height. Thus when assembling the bottom section **150A**, the one foot tubular segment **10A** is surrounded by alternating tubular members **10B** and **10C**.

Referring now to FIGS. **14** and **16**, the fuel basket **1000** further comprises a plurality of resultant cells **20A** that are formed by the outer surface **13** of the walls **11** of six of the tubular members **10**. A single resultant cell **20A** is illustrated in FIG. **14**. Where six tubular members are joined in a polar configuration, a resultant cell **20A** having a hexagonal horizontal cross-sectional profile is formed therebetween. This arrangement allows for less plates **11** (i.e., tubes **10**) to be used to create the same number of cells **20**, thereby creating a lighter fuel basket **1000**. In the illustrated embodiment there are a total of twenty-nine resultant cells **20A**. The invention is not so limited however, and the number of resultant cells may vary. The resultant cells **20A** have about a ½ inch larger opening and thus can accommodate fuel assemblies that are damaged or dimensionally-deviant. Additionally, the resultant cells **20A** allow for the fuel basket **1000** to be fabricated using fillet welds because the resultant cells provide easier access to the tubes **10**.

As best seen in FIG. **16**, some resultant cells **20A** that are located along the periphery of the fuel basket **1000** require the use of a closure plate **15A-B** to complete the cell. The closure plates **15A-B** are par-hexagonal plates. The fuel basket assembly **1000** comprises two types of closure plates **15A-B** depending on the configuration of the resultant cell **20A**.

Some resultant cells **20A** require only a single panel to enclose the cell **20A**, while other resultant cells require two panels to enclose the resultant cell **20A**. Where two panels are required, a closure plate **15A** is formed by bending a plate into two panels of equal length and attaching the lateral edges of the closure plate **15A** to the lateral edges of the tubes **10** that are forming the applicable resultant cell **20A**.

The basket assembly **1000** further comprises basket support tubes **30A, B** placed adjacent the storage grid **1001** along its periphery. The basket support tubes **30A, B** are used to provide conformal contact with the container/vessel in which the basket assembly **100** is to be used. The basket support tubes **30A, B** comprise a par-hexagonal plate **31A, B** connected to the concave side of a curved plate **32A, B**. The curved plates **32A, 32B** form a substantially circular outer perimeter for the fuel basket **1000**. Because the basket support tubes **30A, B** are not located at every position on the periphery of the storage grid, the substantially circular outer perimeter is circumferentially segmented.

For resultant cells **20A** that require only a single panel to form a six-walled cell (i.e. One side is open), the par-hexagonal plate **31B** of the support tubes **30B** can also function as a closure plate. The basket support tubes **30A** can be used where there is no resultant cell **20A**, or where the resultant cell **20A** is enclosed by the closure plate **15A**.

Referring now to FIG. **17**, the basket support tubes **30A, B** are shown removed from the fuel basket assembly **1000**. The basket support tubes **30A, B** are provided so that the basket assembly is centered within the container (which can be a canister or a cask) in which it is to be used.

Referring now to FIG. **18**, the basket assembly **100** with the basket supports **30A, B** attached is illustrated. The basket supports **30A, B** provide for a circular outer perimeter of the fuel basket **1000**. The gaps **31** in the basket supports **30A, B** do not have fuel assemblies stored therein, thus they may improve the cooling of the fuel assemblies stored in the cells **20**.

V. Flux Trap Fuel Basket Embodiment

Referring now to FIG. **19**, a fuel basket **2000** according to another embodiment of the present invention is illustrated. The design aspects of the fuel assembly **2000** are substantially similar to those discussed above with respect to the fuel basket **1000**. To avoid redundancy, only those design aspects of the fuel basket **2000** that substantially differ from the fuel basket **1000** will be discussed.

The basket assembly **2000** comprises a plurality of flux trap spaces **50** that regulate the production of neutron radiation and prevent reactivity in a flooded condition. The flux traps **5** are small spaces that extend the height of the basket **2000**. The flux traps **50** are formed between two of the tubular members **210** that are close to one another and substantially parallel. As will be discussed below, the flux traps **50** are designed to be of variable width to maximize the number of fuel assemblies that can be stored in the fuel basket **2000** while maintaining a reactivity equal to or less than 0.95. The flux traps **50** are formed between the outer surface of the storage tubes **2210**. The tubes **2210** have a plurality of spacers **60** that maintain the spacing between tubular members **10** that forms the flux trap **50**.

Referring now to FIG. **20**, a single storage tube **2210** is shown removed from the fuel basket **2000** so that its design aspects can be more clearly visible. The storage tube **2210** has a hexagonal horizontal cross-sectional profile but can be any configuration. Preferably, the cross-sectional profile will be determined by the type of fuel assembly to be loaded and stored in the fuel basket assembly **2000**. The tube **2210** comprises a plurality of notches **2215**. The notches **2215** provide

spaces through which the spacer **2260** (shown in FIG. **24**) can be attached. Preferably, the spacers **60** are initially tack welded to the tubes **2210** so that the fuel basket **2000** can be assembled. After the fuel basket **2000** is assembled it is placed on its side and the spacers **2260** that are on the bottom (closer to the ground surface on which the basket assembly **2000** is resting) are plug welded to the storage tubes **2210**. This allows for gravity to aid in the welding procedure. The fuel basket **2000** is rotated so that the next set of spacers **2260** is now closer to the ground surface for welding to the tubes **2210**. The rotating and welding procedure is repeated for all of the spacers **2260** and tubes **2210**.

Referring to FIGS. **21** and **22** concurrently, the fuel basket **2000** is formed by a plurality of sections **2250A-F** of the tubular segments **2210A-C** that are arranged in a stacked assembly. The sections **2250A-F** and the tubular segments **2210A-C** are joined with one another to form the stacked assembly that is the fuel basket **2000**. Each section **2250A-F** of the fuel basket **2000** comprises a honeycomb-like grid of tubular segments **2210A-C** arranged in the polar configuration. The tubular members **2210A-C** of the basket assembly **2000** are of three varying heights, each height delineated by the letter A-C. A single bottom section **2250A** of the basket **2000** is illustrated in FIG. **21**, the bottom section **2250A** has tubular segments **2210A-C** arranged in a polar configuration. The middle sections **2250B-E** comprise tubular segments **2210C**, all having the same height. The top section **2250F** comprises tubular segments **210A** arranged so that the top surfaces of the tubular segments **2210A-C** are aligned at the same elevation.

The storage tubes **2210A** have a height that is preferably equal to one foot. The tubular segments **2210B** have a height that is preferably equal to two feet. The tubular segments **2210C** have a height that is preferable equal to three feet. The invention is not so limited however, and the tubular segments **2210A-C** may be of any height so long as the cells formed are at least equal to the height of the fuel assembly. In order that the interfaces **2221** are not aligned, it is preferable that no adjacent tubular segments **2210A-C** of the bottom section **2250A** be of the same height. Thus when assembling the bottom section **2250A**, the one foot tubular segments **2210A** are surrounded by alternating tubular segments **2210B** and **2210C**. The bottom edges of the tubular segments **2210A-C** of the bottom section **2250A** are aligned.

Referring now to FIG. **24**, a top view of the fuel basket **2000** is illustrated. The basket assembly **200** comprises three types of spacers **2260A-C** that form flux traps **50** between the tubes **2210**. The first type of spacer **2260A** is a unilateral triangle that maintains the largest gap between the tubes **2210** located near the central axis of the basket **2000**. In other words, the spacer **2260A** is used with the tubes **2210** that are closest to the center of the basket **2000** because the neutrons emitted by the fuel assemblies in the center of the basket **2000** cannot easily escape to the perimeter of the basket **2000**. Thus, for maintaining a reactivity of less than 0.95, a larger flux trap **50** is required. A second shape of spacer **2260B** is used between the storage tubes **2210** that are nearer the outer perimeter of the fuel basket **2000**. A rectangular spacer **2260C** is used for the storage tubes **2210** that are nearest to the outer perimeter formed by basket supports **2230A,B**.

The fuel baskets **1000, 2000** of the present invention are not limited to use with any particular type of surrounding vessels. For example, in one embodiment, the basket assemblies **1000, 2000** can be incorporated into a hermetically sealable multi-purpose canister for use in conjunction with VVO style containment systems. In such an embodiment, the basket assemblies **1000, 2000** will be provided in a cavity formed by

a cylindrical metal shell. The metal shell will encircle the basket assembly **1000, 2000** and a metal base plate may be welded to the bottom of the metal shell. A metal closure plate can be fitted on top of the cylinder formed by the metal shell, thereby forming a canister. Thermally conductive casks can also be used to house the fuel baskets **1000, 2000** directly.

While the invention has been described and illustrated in sufficient detail that those skilled in this art can readily make and use it, various alternatives, modifications, and improvements should become readily apparent without departing from the spirit and scope of the invention.

What is claimed is:

1. A fuel basket or fuel rack for supporting radioactive fuel assemblies comprising:
 - a grid of cells for housing radioactive fuel assemblies, the grid formed by a plurality of tubes having inner surfaces that form the cells, the tubes arranged in an adjacent manner;
 - each of the tubes formed by a plurality of tubular segments stacked in axial alignment, an interface formed between adjacent tubular segments of each tube; and
 - wherein lengths of the tubular segments and a pattern in which the tubes are arranged to form the grid is such that none of the interfaces of adjacent tubes are aligned with one another.
2. The fuel basket or fuel rack of claim 1 wherein all of the tubular segments are selected from one of only three different lengths.
3. The fuel basket or fuel rack of claim 1 wherein the tubes are hexagonal tubes.
4. The apparatus fuel basket or fuel rack of claim 1 wherein the tubes are constructed of a boron impregnated aluminum material.
5. The apparatus fuel basket or fuel rack of claim 1 wherein all of the tubes have approximately the same length.
6. The fuel basket or fuel rack of claim 1 further comprising the tubes arranged in a pattern so that one or more of the cells is a resultant cell formed by the outside surfaces of surrounding tubes.
7. A fuel basket or fuel rack for supporting radioactive fuel assemblies comprising:
 - a bottom section comprising a plurality of bottom tubular segments of varying length, the bottom tubular segments arranged in an axially adjacent manner and in a pattern wherein no two adjacent bottom tubular segments are the same length, bottom edges of the bottom tubular segments being aligned;
 - a middle section comprising a plurality of middle tubular segments of equal length, the middle section stacked atop the bottom section wherein the middle tubular segments are axially aligned with the bottom tubular segments and bottom edges of the middle tubular segments abut top edges of the bottom tubular segments; and
 - a top section comprising a plurality of top tubular segments of varying length, the top section stacked atop the middle section wherein the top tubular segments are axially aligned with the middle tubular segments, bottom edges of the top tubular segments abut top edges of the middle tubular segments, and top edges of the top tubular segments are aligned.
8. A fuel basket for supporting radioactive fuel assemblies comprising:
 - a plurality of tubes having an internal cavity for receiving a radioactive fuel assembly;
 - the tubes arranged in a substantially vertical orientation and spaced from one another so that a flux trap space

19

exists between all adjacent tubes, the tubes forming a storage grid having a central axis and a perimeter; a plurality of spacers positioned in the flux trap spaces for maintaining the existence of the flux trap spaces; and wherein the width of the flux trap space between adjacent tubes decreases with distance from the central axis of the storage grid.

9. The fuel basket of claim 8 further comprising: the tubes being hexagonal tubes;

a plurality of support tubes comprising a par-hexagonal plate connected to a curved plate; and

the plurality of support tubes arranged adjacent to the hexagonal tubes along the perimeter of the storage grid so that the curved plates define a substantially circular outer perimeter, thereby forming a basket assembly.

10. The fuel basket of claim 9 further comprising: a container having an inner surface forming a substantially cylindrical cavity; and

the basket assembly positioned within the cylindrical cavity of the container, the curved plates being in contact with the inner surface of the container.

11. The fuel basket of claim 10 wherein the tubes comprise one or more cutouts at the bottom edges that form passageways between the internal cavities.

12. The fuel basket of claim 8 wherein the tubes being hexagonal tubes; and each of the spacers located within the flux trap spaces contacts edges of three adjacent hexagonal tubes.

13. The fuel basket of claim 12 wherein the spacers are rods.

14. The fuel basket of claim 13 wherein the rods have a generally truncated-triangular horizontal cross-section.

15. The fuel basket of claim 8 further comprising:

wherein the tubes are hexagonal tubes; and

wherein the spacers are rods, each of the rods comprise three grooves extending axially along a length of the rods, the three grooves circumferentially spaced in a symmetric manner about an axis of the rods, the rods positioned in the flux trap spaces so that edges of the hexagonal tubes nest in the grooves.

16. The fuel basket of claim 15 wherein the tubes are constructed of a boron impregnated aluminum material.

17. A fuel basket or fuel rack for supporting radioactive fuel assemblies comprising:

20

a bottom section comprising a plurality of bottom tubular segments of varying length, the bottom tubular segments arranged in an axially adjacent manner and in a pattern wherein no two adjacent bottom tubular segments are the same length, bottom edges of the bottom tubular segments being aligned;

a plurality of middle sections comprising an uppermost middle section and a lowermost middle section, each of the uppermost and lowermost middle sections comprising a plurality of middle tubular segments of equal length, the lowermost middle section stacked atop the bottom section wherein the middle tubular segments of the lowermost middle section are axially aligned with the bottom tubular segments and bottom edges of the middle tubular segments of the lowermost middle section abut top edges of the bottom tubular segments; and

a top section comprising a plurality of top tubular segments of varying length, the top section stacked atop the uppermost middle section wherein the top tubular segments are axially aligned with the middle tubular segments of the uppermost middle section, bottom edges of the top tubular segments abut top edges of the middle tubular segments of the uppermost middle section, and top edges of the top tubular segments are aligned.

18. The fuel basket or fuel rack of claim 17 wherein the middle tubular segments of the uppermost middle section are axially aligned with the middle tubular segments of the lowermost middle section and wherein bottom edges of the middle tubular segments of the uppermost middle section abut top edges of the middle tubular segments of the lowermost middle section.

19. The fuel basket or fuel rack of claim 17 further comprising an intermediate middle section comprising a plurality of middle tubular segments of equal length and wherein the middle tubular segments of the intermediate middle section are axially aligned with the middle tubular segments of each of the lowermost and uppermost middle sections and wherein bottom edges of the middle tubular segments of the intermediate middle section abut top edges of the middle tubular segments of the lowermost middle section and wherein bottom edges of the middle tubular segments of the uppermost middle section abut top edges of the middle tubular segments of the intermediate middle section.

* * * * *